

◆ 球磨机 Ball mill

球磨机适用于粉磨各种矿石及其它物料，被广泛用于选矿，建材及化工等行业，可分为干式和湿式两种磨矿方式。根据排矿方式不同，可分格子型和溢流型两种。

Ball mills are used primary for single stage fine grinding. It is the key equipment that repulverizes the material after it is crushed, which is widely used in the manufacture industries, such as cement, silicate, new building material, refractory material, fertilizer, mill run of ferrous metal, nonferrous metal and glass ceramics and can be used for the dry and wet pulverization for all kinds of ores and other grindable materials.



规格与性能参数表 Specifications:

规格型号 Model	筒体转速 Speed of Bucket (r/min)	装球量 Weight of Ball (t)	给料粒度 Size of Feed Opening (mm)	出料粒度 Size of Outputting (mm)	产量 Capacity (t/h)	电机功率 Power (kw)	重量 Weight (t)
φ900×1800	38	1.5	≤20	0.075-0.89	0.65-2	18.5	3.6
φ1200×2400	32	3.8	≤25	0.075-0.6	1.5-4.8	45	12.5
φ1200×4500	32	7	≤25	0.074-0.4	1.6-5.8	55	13.8
φ1500×3000	27	8	≤25	0.074-0.4	2-5	90	17
φ1500×5700	27	15	≤25	0.074-0.4	3.5-6	132	24.7
φ1830×3000	24	11	≤25	0.074-0.4	4-10	180	28
φ1830×6400	24	23	≤25	0.074-0.4	6.5-15	210	34
φ1830×7000	24	25	≤25	0.074-0.4	7.5-17	245	36
φ2200×5500	21	30	≤25	0.074-0.4	10-22	370	48.5
φ2200×7500	21	33	≤25	0.074-0.4	16-29	475	56

注：表中产量和细度以石灰石为例，各项参数及外形若有变更，依发货时随机附带的使用维护说明书为准。
Notes: If there is any modification, all parameter and overall dimension are subject to the operating instructions.